



BUNTON® HYDRO WALK-BEHIND MOWER



**Smooth operation from start to finish.
Maximum productivity and true zero-turn radius.**

Specifications, while correct at the time of printing, may change without notice.

Bunton® is a registered trademark of Commercial Grounds Care, Inc.
© 2006 CGC, Inc. • One Bob Cat Lane • Johnson Creek, WI 53038 • www.buntonturf.com

BUNTON® HYDRO WALK-BEHIND MOWER

POWER

15 hp KAWASAKI

Engine	15-HP (11.2 kW) Kawasaki, V-twin, air-cooled, gas
Ignition	Electronic with recoil start
Fuel Capacity	4.2 gal. (16.1 l) Polyethylene tank
Lubrication	Pressure with filter
Air Cleaner.....	Ducted dual element

17 hp KAWASAKI

Engine	17-HP (12.7 kW) Kawasaki, V-twin, air-cooled, gas
Ignition	Electronic with recoil start
Fuel Capacity	4.2 gal. (16.1 l) Polyethylene tank
Lubrication	Pressure with filter
Air Cleaner.....	Ducted dual element

21 HP KAWASAKI

Engine.....	21-HP (15.7 kW) Kawasaki V-twin, air-cooled, gas
Ignition	Electronic with recoil start
Fuel Capacity	4.2 gal. (16.1 l) Polyethylene tank
Lubrication	Pressure with filter
Air Cleaner	Ducted dual element

17 hp KAWASAKI

Engine	17-HP (12.7 kW) Kawasaki, V-twin, air-cooled, gas
Ignition	Electric start
Fuel Capacity	4.2 gal. (16.1 l) Polyethylene tank
Lubrication	Pressure with filter
Air Cleaner.....	Ducted dual element

DRIVETRAIN

Transmission	Hydrostatic drive with dual pumps and wheel motors
Axle.....	1 in. (25 mm) diameter
Drive	Belt from engine to hydro input shafts; hydrostatic drive to wheels
Hydraulic Capacity	1.2 gal. (4.6 l) with 25-micron filtration
Brakes.....	Hydrostatic provides dynamic braking; dual-wheel parking brake
Tires	All Models Rear: (2) 16 x 6.50-8 4-ply turf tread tubeless
Fixed Deck Front:	(2) 9 x 3.50-4 4-ply smooth tread with tube
Floating Deck Front:	(2) 11 x 4.00-5 4-ply smooth tread with tube
Anti-scalping	Smooth-tread pneumatic caster wheels
Steering	Patented Z-Control handles control independent power to each wheel for moving, stopping and power turning
Controls.....	Throttle; speed selector/tracking levers; wheel drive traction levers with locks; blade drive switch; dual-wheel parking brake; operator-presence controls; keyed on/off switch (on/off/start switch on electric start models)
Speed (maximum)	6 mph (9.6 km/h) forward; 2 mph (3.2 km/h) reverse
Turning Radius	True zero

DIMENSIONS

Overall Length With 61" Deck	77.9 in. (1.97 m)
Overall Length With 36" Deck	77.2 in. (1.96 m)
Width with 61" Deck.....	72.9 in. (1.85 m)
Width with 36" Deck	47 in. (1.19 m)
Height	40.3 in. (1.02 m)

Weight

21 hp	380 lbs. (172 kg)
17-hp	256 lbs. (116 kg)
15-hp	269 lbs. (122 kg)

ACCESSORIES

Jumbo grass catcher; Mulcherizer™ mulching kit; striping kit

Specifications, while correct at the time of printing, may change without notice.

Bunton® is a registered trademark of Commercial Grounds Care, Inc.
© 2006 CGC, Inc. • One Bob Cat Lane • Johnson Creek, WI 53038 • www.buntonturf.com